

## Karakteristike

top



- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Gladka sprednja plošča se lahko prilagodi z logotipi, lužmi, žrkami ali varnostnimi in informativnimi signali glede na zahteve narožnika.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Druge barve so na voljo po želji.
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Druge barve so na voljo po želji.
- Anodizirani aluminijasti odhondi ventili oblikovani z zražnim profilom.
- Nizkohrupni navkrižno prepleteni ventilatorji, ki jih poganja 2-stopenjski motor z zunanjim rotorjem.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. Tip "E" z zašžitenimi elektrižnimi elementi, tremi stopnjami z integrirano regulacijo. Tip "A" brez ogrevanja, samo zrak.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

## Specifikacije

50Hz

### Neogrevano

Model	(m <sup>3</sup> /h)	(m)
TOP 1000 A	3.5	
TOP 1500 A	3.5	
TOP 2000 A	3.5	

### Elektrižno ogrevanje

Model	(m <sup>3</sup> /h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

### Vodno ogrevanje

Model	(m <sup>3</sup> /h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

Dimenzije

